



- Note :**
- Pin 1 : Bottom**
  - Pin 2 : Top**
  - Pin 3 : Left**
  - Pin 4 : Right**
  - Pin Pitch : 2.54 mm**
  - Total Thickness : 3.6 ± 0.2 mm**
  - Surface Hardness : 3H**
  - Optical Clarity : 76 %**
  - Operating Temperature : 0°C ~ 50°C**
  - Endurance Test : Over 1 million strikes**
  - Operating Voltage : DC5-12V**
  - Resistance : 200Ω ~ 900Ω**
  - Linearity : < 1.5%**
  - Faceplate Surface : Anti-glare coating**
  - Operation Pressure : 35g~60g**
  - Storage Temperature : -20°C ~ 70°C**
  - Message Noise : 5 m sec ~ 15 m sec**
  - Operating Current : 5mA ~ 25mA**
  - Isolation Resistance : DC25V 20MΩ ↑**

|          |           |  |  |  |         |            |                |
|----------|-----------|--|--|--|---------|------------|----------------|
| Model No | SE-AM1402 |  |  |  | Unit:mm | Date       | 9 - 25 - 1997  |
|          |           |  | <b>SUPER ELITE TECHNOLOGY CO., LTD</b> |  |         | Chang Date | 02 - 25 - 1999 |