

# NPN SILICON RF POWER TRANSISTOR

**DESCRIPTION:**

The **ASI MLN1037F** is Designed for

**FEATURES:**

- 
- 
- **Omnigold™** Metalization System

**MAXIMUM RATINGS**

<b>I<sub>C</sub></b>	10 A
<b>V<sub>CB</sub></b>	60 V
<b>V<sub>CE</sub></b>	35 V
<b>P<sub>DISS</sub></b>	140 W @ T <sub>C</sub> = 25 °C
<b>T<sub>J</sub></b>	-65 °C to +200 °C
<b>T<sub>STG</sub></b>	-65 °C to +150 °C
<b>θ<sub>JC</sub></b>	5.5 °C/W

**PACKAGE STYLE .250 2L FLG**

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.028 / 0.71	.032 / 0.81
B	.740 / 18.80	
C	.245 / 6.22	.255 / 6.48
D	.128 / 3.25	.132 / 3.35
E		.125 / 3.18
F	.110 / 2.79	.117 / 2.97
G		.117 / 2.97
H	.560 / 14.22	.570 / 14.48
I	.790 / 20.07	.810 / 20.57
J	.225 / 5.72	.235 / 5.97
K	.165 / 4.19	.185 / 4.70
L	.003 / 0.08	.007 / 0.18
M	.058 / 1.47	.068 / 1.73
N	.119 / 3.02	.135 / 3.43
P	.149 / 3.78	.187 / 4.75

**ORDER CODE: ASI10628**

**CHARACTERISTICS** T<sub>C</sub> = 25 °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
<b>BV<sub>CEO</sub></b>	I <sub>C</sub> = 50 mA	35			V
<b>BV<sub>CER</sub></b>	I <sub>C</sub> = 50 mA      R <sub>BE</sub> = 10 Ω	60			V
<b>BV<sub>EBO</sub></b>	I <sub>E</sub> = 10 mA	4.0			V
<b>I<sub>CES</sub></b>	V <sub>E</sub> = 28 V			5	mA
<b>h<sub>FE</sub></b>	V <sub>CE</sub> = 5.0 V      I <sub>C</sub> = 1.0 A	10		100	---
<b>C<sub>ob</sub></b>	V <sub>CB</sub> = 28 V      f = 1.0 MHz			15	pF
<b>P<sub>GE</sub></b>	V <sub>CE</sub> = 20 V      I <sub>CQ</sub> = 800 mA      f = 1.0 GHz P <sub>OUT</sub> = 5.0 W	10			dB