


# Schottky Barrier Diodes (Surface Mount) 60V, 90V


Parameter Type No.	Absolute Maximum Ratings					Electrical Characteristics (Ta=25°C)					Others			
	VRM (V)	IF(AV) (A)	IFSM (A) 50Hz Half-cycle Sinewave Single Shot	Tj (°C)	Tstg (°C)	VF (V)		IR (mA)	IR (H) (mA)	trr (ns)	Rth(j-ℓ) (°C/W)	Mass (g)	Fig.	
						max	IF (A)	VR=VRM max	VR=VRM Ta=100°C max					
SFPB-56	60	0.7	10	-40 to +150		0.62	0.7	1.00	7.5	100	100/100	20.0	0.072	Ⓐ
SFPB-66		2.0	25			0.69	2.0	1.0	15					
SFPB-76		2.0	40			0.62	2.0	2.00	20					
SFPB-59	90	0.7	10			0.81	0.7	1.00	5					
SFPB-69 *		1.5	40											

\* Under development



## SFPB-56



## SFPB-66




## SFPB-76




**SFPB-59**


**Ta—If(AV) Derating**




**V<sub>F</sub>—I<sub>F</sub> Characteristics (Typical)**



**V<sub>R</sub>—I<sub>R</sub> Characteristics (Typical)**




**I<sub>FMS</sub> Rating**




**SFPB-69**


**T<sub>l</sub>—I<sub>F(AV)</sub> Characteristics**



**V<sub>F</sub>—I<sub>F</sub> Characteristics (Typical)**



**V<sub>R</sub>—I<sub>R</sub> Characteristics (Typical)**



**I<sub>FMS</sub> Rating**

