

SKKE 1200



SEMIPACK® 6

Rectifier Diode Modules

SKKE 1200

Target Data

Features

- Precise metal pressure contacts for high reliability

Typical Applications


- Rectifiers

V_{RSM} V	V_{RRM} V	$I_{FRMS} = 2000\text{ A}$ (maximum value for continuous operation) $I_{FAV} = 1180\text{ A}$ (sin. 180; $T_c = 100\text{ °C}$)		
1900	1800	SKKE 1200/18 H4		
2300	2200	SKKE 1200/22 H4		

Symbol	Conditions	Values	Units
I_{FAV}	sin. 180; $T_c = 100\text{ °C}$	1180	A
I_{FSM}	$T_{vj} = 25\text{ °C}$; 10 ms	45000	A
	$T_{vj} = 160\text{ °C}$; 10 ms	40000	A
i^2t	$T_{vj} = 25\text{ °C}$; 8,3 ... 10 ms	10125000	A²s
	$T_{vj} = 160\text{ °C}$; 8,3 ... 10 ms	8000000	A²s
V_F	$T_{vj} = 25\text{ °C}$; $I_F = 3000\text{ A}$	max. 1,4	V
$V_{(TO)}$	$T_{vj} = 160\text{ °C}$	max. 0,75	V
r_T	$T_{vj} = 160\text{ °C}$	max. 0,17	mΩ
I_{RD}	$T_{vj} = 160\text{ °C}$; $V_{RD} = V_{RRM}$	max. 60	mA
$R_{th(j-c)}$	cont.	0,0395	K/W
	sin. 180	0,041	K/W
$R_{th(c-s)}$		0,01	K/W
T_{vj}		- 40 ... + 160	°C
T_{stg}		- 40 ... + 125	°C
V_{isol}	a. c. 50 Hz; r.m.s.; 1 s / 1 min.	4800 / 4000	V~
M_s	to heatsink	$6 \pm 15\%$	Nm
M_t	to terminals	$18 \pm 15\%$	Nm
a		$5 * 9,81$	m/s²
m	approx.	2150	g
Case		A82	



SKKE



This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.