

- Low Input Currents
- Low Input Offset Parameters
- Frequency and Transient Response Characteristics Adjustable
- Short-Circuit Protection
- Offset-Voltage Null Capability
- No Latch-Up
- Wide Common-Mode and Differential Voltage Ranges
- Same Pin Assignments as  $\mu$ A748,  $\mu$ A709, LM101A/LM301 except U Package

**description**


The  $\mu$ A777 is a precision operational amplifier. Low offset and bias currents improve system accuracy when used in applications such as long-term integrators, sample-and-hold circuits, and high-source-impedance summing amplifiers. This device is an excellent choice where a performance between that of super-beta and general purpose operational amplifiers is required.

External compensation of the  $\mu$ A777 may be implemented in either normal or feed-forward configuration to satisfy bandwidth and slew-rate requirements. This circuit features high gain, wide differential and common-mode input voltage range, output short-circuit protection, and null capability.


The  $\mu$ A777C is characterized for operation from 0°C to 70°C.

**terminal assignments**

**JG OR P DUAL-IN-LINE  
PACKAGE (TOP VIEW)**




**J OR N DUAL-IN-LINE  
PACKAGE (TOP VIEW)**



NC—No internal connection.

**schematic**



Resistor values shown are nominal and in ohms.

Copyright © 1979 by Texas Instruments Incorporated

# TYPE $\mu$ A777C HIGH-PERFORMANCE OPERATIONAL AMPLIFIER

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

		$\mu$ A777C	UNIT
Supply voltage $V_{CC+}$ (see Note 1)		22	V
Supply voltage $V_{CC-}$ (see Note 1)		-22	V
Differential input voltage (see Note 2)		$\pm 30$	V
Input voltage (either input, see Notes 1 and 3)		$\pm 15$	V
Voltage between either offset null terminal (N1/N2) and $V_{CC-}$		-0.5 to 2	V
Duration of output short-circuit (see Note 4)		unlimited	
Continuous total dissipation at (or below) 25°C free-air temperature (see Note 5)		500	mW
Operating free-air temperature range		0 to 70	°C
Storage temperature range		-65 to 150	°C
Lead temperature 1/16 inch (1,6 mm) from case for 60 seconds		J or JG package	300
Lead temperature 1/16 inch (1,6 mm) from case for 10 seconds		N or P package	260

- NOTES: 1. All voltage values, unless otherwise noted, are with respect to the midpoint between  $V_{CC+}$  and  $V_{CC-}$ .  
 2. Differential voltages are at the noninverting input terminal with respect to the inverting input terminal.  
 3. The magnitude of the input voltage must never exceed the magnitude of the supply voltage or 15 volts, whichever is less.  
 4. The output may be shorted to ground or either power supply.  
 5. For operation above 25°C free-air temperature, refer to Dissipation Derating Table. In the J and JG package,  $\mu$ A777C chips are glass-mounted.

electrical characteristics at specified free-air temperature,  $V_{CC+} = 15$  V,  $V_{CC-} = -15$  V,  $C_C = 30$  pF  
(unless otherwise noted)

PARAMETER	TEST CONDITIONS†	MIN	TYP	MAX	UNIT
$V_{IO}$ Input offset voltage	$R_S \leq 50$ k $\Omega$	25°C		0.7	5
		0°C to 70°C			5
$\alpha_{VIO}$ Average temperature coefficient of input offset voltage	$R_S \leq 50$ k $\Omega$	0°C to 70°C		4	30
$I_{IO}$ Input offset current		25°C		0.7	20
		0°C to 70°C			40
$\alpha_{IIO}$ Average temperature coefficient of input offset current		0°C to 25°C		20	600
		25°C to 70°C		10	300
$I_{IB}$ Input bias current		25°C		25	100
		0°C to 70°C			200
$V_{ICR}$ Common-mode input voltage range		0°C to 70°C		$\pm 12$	$\pm 13$
$V_{OPP}$ Maximum peak-to-peak output voltage swing	$R_L = 10$ k $\Omega$	0°C to 70°C		24	28
	$R_L = 2$ k $\Omega$	0°C to 70°C		20	26
$A_{VD}$ Large-signal differential voltage amplification	$V_O = \pm 10$ V, $R_L \geq 2$ k $\Omega$	25°C		25	250
		0°C to 70°C		15	
$r_i$ Input resistance		25°C		1	2
$r_o$ Output resistance		25°C			100
$C_i$ Input capacitance		25°C			3
CMRR Common-mode rejection ratio	$R_S = 50$ k $\Omega$	0°C to 70°C		70	95
$k_{SVR}$ Supply voltage rejection ratio ( $\Delta V_{CC}/\Delta V_{IO}$ )	$R_S \leq 50$ k $\Omega$	0°C to 70°C		15	150
$I_{OS}$ Short-circuit output current		25°C		$\pm 25$	
		0°C		1.9	3.3
$I_{CC}$ Supply current	No load, No signal	25°C			3.3
		70°C			3.3

† All characteristics are specified under open-loop operation.

# TYPE $\mu$ A777C HIGH-PERFORMANCE OPERATIONAL AMPLIFIER

operating characteristics,  $V_{CC+} = 15\text{ V}$ ,  $V_{CC-} = -15\text{ V}$ ,  $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	$\mu$ A777C			UNIT
		MIN	TYP	MAX	
$t_r$ Rise time	$V_I = 20\text{ mV}$ , $R_L = 2\text{ k}\Omega$ , $C_L = 100\text{ pF}$	$A_V = 1$ , $C_C = 30\text{ pF}$	0.3		$\mu\text{s}$
		$A_V = 10$ , $C_C = 3.5\text{ pF}$	0.2		
Overshoot factor	$V_I = 20\text{ mV}$ , $R_L = 2\text{ k}\Omega$ , $C_L = 100\text{ pF}$	$A_V = 1$ , $C_C = 30\text{ pF}$	5%		
		$A_V = 10$ , $C_C = 3.5\text{ pF}$	5%		
SR Slew rate	$R_L = 2\text{ k}\Omega$ , $C_L = 100\text{ pF}$	$A_V = 1$ , $C_C = 30\text{ pF}$	0.5		$\text{V}/\mu\text{s}$
		$A_V = 10$ , $C_C = 3.5\text{ pF}$	5.5		

## PARAMETER MEASUREMENT INFORMATION




FIGURE 1—RISE TIME, OVERSHOOT, AND SLEW RATE

## DISSIPATION DERATING TABLE

PACKAGE	POWER RATING	DERATING FACTOR	ABOVE $T_A$
J (Alloy-Mounted Chip)	500 mW	$11.0\text{ mW}/^\circ\text{C}$	$105^\circ\text{C}$
J (Glass-Mounted Chip)	500 mW	$8.2\text{ mW}/^\circ\text{C}$	$89^\circ\text{C}$
JG (Alloy-Mounted Chip)	500 mW	$8.4\text{ mW}/^\circ\text{C}$	$90^\circ\text{C}$
JG (Glass-Mounted Chip)	500 mW	$6.6\text{ mW}/^\circ\text{C}$	$74^\circ\text{C}$
N	500 mW	$9.2\text{ mW}/^\circ\text{C}$	$96^\circ\text{C}$
P	500 mW	$8.0\text{ mW}/^\circ\text{C}$	$87^\circ\text{C}$

Also see Dissipation Derating Curves, Section 2.

# TYPE $\mu$ A777C HIGH-PERFORMANCE OPERATIONAL AMPLIFIER

## TYPICAL CHARACTERISTICS




FIGURE 2




FIGURE 3—INVERTING CIRCUIT WITH UNITY GAIN  
AND FEED-FORWARD COMPENSATION

## TYPICAL APPLICATION DATA




FIGURE 4—INVERTING CIRCUIT WITH ADJUSTABLE GAIN,  
SINGLE-POLE COMPENSATION, AND OFFSET ADJUSTMENT